


STANDARD EQUIPMENT

- High-frequency electronic plant 24V with microprocessor fault research
- 24V 160Ah traction battery
- Electronic 24V 30A battery charger with microprocessor
- Fixed forks 1150 mm. long
- 200 mm. free lift (except for 3500 mm. lifting)
- Folding footboard with lateral protections
- Ignition key switch
- Digital hour-meter
- Double swinging front rollers
- Double push-button and lever control for forks
- Electric limit switch
- Braking in release in contraflow
- Electromagnetic parking brake
- Shock absorber on driving-wheel
- Chromed aerodynamic piston
- Emergency push-button
- Safety push-button for accident prevention
- Automatic speed reduction
- Stabilising wheels with extra-heavy brackets
- Manual release of traction group
- Acoustic warning signal
- Battery discharged warning indicator
- Shock resistant ergonomic steering rudder
- Steering with gas spring for the controls release in vertical position



The trucks are fitted with a shock absorber system that ensures perfect contact of the driving wheel with the floor, even in the case of deep bumps.



XDUB



INOX AVAILABLE

model	XDUB 1216	XDUB 1516	XDUB 1225	XDUB 1525	XDUB 1230	XDUB 1530	XDUB 1235	XDUB 1535
Q kg	1200	1500	1200	1500	1200	1500	1200	1500
C mm	600		600		600		600	
I mm	1150		1150		1150		1150	
L mm	1895	1915	1930	1950	1930	1950	1930	1950
X mm	380		415		415		415	
X2 mm	175		175		175		175	
Y mm	1340	1360	1340	1360	1340	1360	1340	1360
L2 mm	745	765	780	800	780	800	780	800
M mm	530		530		530		530	
N mm	160		160		160		160	
h1 mm	1990		1740		1990		2240	
h2 mm	1450		200		200		/	
h3 mm	1600		2500		3000		3500	
h4 mm	2120		3020		3520		4020	
B mm	840		840		840		1000*	
WA* mm	1660		1660		1660		1660	
WA** mm	1980		1980		1980		1980	

Closed folding footboard ** Open folding footboard




Diagram representing the position variation of the load transporter with the variation of the same.




Diagram of maximum loads regarding the lifts.

