

STANDARD EQUIPMENT

- Electronic 24V separate excitation system with energy feedback braking
- 24V 160Ah traction battery
- Electronic 24V 30A battery charger with microprocessor
- Fixed forks 1150 mm. long
- 200 mm. lifting
- Order picker with 900 mm. operator lifting (PLUS)
- Push-button forks controls
- Proof-seal bearings and pins with selflubricating sintered bushings
- Double swinging front rollers
- Electric limit switch
- Electromagnetic parking brake
- Protection fuse
- Shock absorber on driving-wheel
- Ignition switch with key
- Chromed oleodynamic piston
- Emergency push-button
- Safety push-button for accident prevention
- Stabilising wheels with extra-heavy brackets
- Manual release of traction group
- Acoustic warning signal
- Battery discharged warning indicator
- Shock resistant ergonomic steering rudder



XTSK



XTSKP



The trucks are fitted with a shock absorber system that ensures perfect contact of the driving wheel with the floor, even in the case of deep bumps.

| model | XTSK XTSKP 1502 | XTSK XTSKP 2002 | XTSK XTSKP 2502 | XTSK 3002 |
|-------|-----------------------|-----------------------|-----------------------|--------------|
| Q kg | 1500 | 2000 | 2500 | 3000 |
| C mm | 600 | 600 | 600 | 600 |
| I mm | 1150 | 1150 | 1150 | 1150 |
| L mm | 2150 | 2150 | 2150 | 2150 |
| X mm | 180 | 180 | 180 | 180 |
| X2 mm | 190 | 190 | 190 | 190 |
| Y mm | 1780 | 1780 | 1780 | 1780 |
| L2 mm | 555 | 555 | 555 | 555 |
| N mm | 540 | 540 | 540 | 540 |
| N mm | 170 | 170 | 170 | 170 |
| h1 mm | 1090 | 1090 | 1090 | 1090 |
| h3 mm | 200 | 200 | 200 | 200 |
| B mm | 750 | 750 | 750 | 750 |
| WA mm | 2000 | 2000 | 2000 | 2000 |

